



ACU Series Oscillating Industrial Unassembled Circulators Data Sheet

General Characteristics of ACU Series Oscillating Industrial Circulators

The ACU Series air circulators are used for both commercial and industrial use.

For indoor or outdoor use.

For outdoor use protection may be needed from the elements.

The blades are steel hub/spider aluminum paddle blades.

Comes with coated steel guards.

The pedestal base has an option of a wheel kit.

Pedestal steel dome base is 27" in diameter and has 5 carriage bolts.

Pedestal pole adjusts in the center of the fan from 52" to 78" inches.

Cord: type 3 conductor, 12ft long.

Also comes with pull chain switch.

Motor Specs: 2 speed, 1 phase, 120V, ball bearing system, totally enclosed and permanently lubricated, permanent split capacitor, 48" frame and 1/2" shaft.

Motor blades, guards and mount are packed in a single carton.

Note: Oscillating motors can only be mounted, where the motor can be mounted in the upright position.

Meets OSHA Oscillating and are ETL-CETL listed.

Made in the U.S.A. with domestic and foreign components.



Used for both industrial and commercial use.

It is used to cool offices, factories, shops, bakeries, laundries, gymnasiums, warehouses, and virtually any place where a high volume of air movement is needed.

For indoor and outdoor use. For use outdoors protection may be needed from the elements.

Warranty of ACU Series Oscillating Industrial Circulators

Manufacturer's Limited Warranty: 1 year




| Specific Characteristics of ACU Series Standard Industrial Maximum Duty Circulators | | | | | | | | | | | | | | | |
|---|--------------------|-----------------|-----------|-----------|--------------|--------------|-----|------|-----|-------|------------|---------------------|-------|--------------------------------------|-----------|
| Item # | Manufacturing # | Blade Ø(In.) | CFM | CFM Volts | Amperes A | Phases PH | HP | RPM | | Speed | Mount Type | Wheel Kit Option | Color | Weight and Dimensions with Packaging | |
| | | | High Low | | | | | High | Low | | | | | Lbs. | L,W,H In. |
| USVNA-001 | ACU 24-PO | 24 | 4500 3600 | 120 | 2.5 | 1 | 1/4 | 1100 | 800 | 2 | Pedestal | - | Gray | 81 | 16,29,29 |
| USVNA-002 | ACU 24-PO + ACM-WK | 24 | 4500 3600 | 120 | 2.5 | 1 | 1/4 | 1100 | 800 | 2 | Pedestal | With | Gray | 85 | 16,29,29 |
| USVNA-003 | ACU 24-WO | 24 | 5400 4300 | 120 | 2.7 | 1 | 1/4 | 1100 | 800 | 2 | Wall | - | Gray | 51 | 16,29,29 |
| USVNA-004 | ACU 30-PO | 30 | 4500 3600 | 120 | 2.5 | 1 | 1/4 | 1100 | 800 | 2 | Pedestal | - | Gray | 84 | 16,35,35 |
| USVNA-005 | ACU 30-PO + ACM-WK | 30 | 4500 3600 | 120 | 2.5 | 1 | 1/4 | 1100 | 800 | 2 | Pedestal | With | Gray | 88 | 16,35,35 |
| USVNA-006 | ACU 30-WO | 30 | 5400 4300 | 120 | 2.7 | 1 | 1/4 | 1100 | 800 | 2 | Wall | - | Gray | 54 | 16,35,35 |





ACU Series Oscillating Industrial Unassembled Circulators Data Sheet

| Dimensions (In.) of ACU Series Oscillating Industrial Circulators | | | | | | |
|---|-------------|------------|-------------|--|--|--|
| Series | Length A | Width B | Height C | | | |
| USCVT-001 to 003 | 14.5" | 27" | 27" | | | |
| USCVT-004 to 006 | 14.5" | 33.5" | 33.5" | | | |



Mounting Options of ACU Series Oscillating Industrial Circulators







| Short Description of ACU Series Oscillating Industrial Circulators | | | | | | | | | | |
|--|--------------------|--|--|--|--|--|--|--|--|--|
| Item # | Manufacturing # | Short Description 70 Characters Maximum | | | | | | | | |
| iteili # | | 0123456789012345678901234567890123456789012345678901234567890123456789 | | | | | | | | |
| USVNA-001 | ACU 24-PO | 24", 4500CFM, 120V, 2.5A, 1PH, 1/4HP, 1100RPM, 2Spd, Pedestal, Gray. | | | | | | | | |

SEO Table of ACU Series Oscillating Industrial Circulators

Title

TPI ACU Series Oscillating Industrial Circulators

Meta Description

TPI ACU Series Oscillating Industrial Circulators for Industrial Use, TPI ACU Series Oscillating Industrial Circulators for Commercial use, TPI ACU Series Oscillating Industrial Circulators for Indoor Use, TPI ACU Series Oscillating Industrial Circulators for Outdoor Use, TPI ACU Series Oscillating Industrial Circulators for Cooling Use, TPI ACU Series Oscillating Industrial Circulators for High Volume Air Movement Use.

Meta Key Words

TPI ACU Series Oscillating Industrial Circulators for Industrial Use, TPI ACU Series Oscillating Industrial Circulators for Commercial use, TPI ACU Series Oscillating Industrial Circulators for Indoor Use, TPI ACU Series Oscillating Industrial Circulators for Outdoor Use, TPI ACU Series Oscillating Industrial Circulators for Cooling Use, TPI ACU Series Oscillating Industrial Circulators for High Volume Air Movement Use.

Meta URL (file name)

Tpi-acu-series-oscillating-industrial-circulators-us-english.htm





ACU Series Oscillating Industrial Unassembled Circulators Data Sheet

Product Line Description of ACU Series Oscillating Industrial Circulators

Type: TPI ACU Series Oscillating Industrial Circulators

Motor Type: Totally Enclosed

Manufacturer: TPI
br>

Model Series: ACU Series

Voltage: 120V

Horse Power: 1/4Hp

Diameter: 24" & 30"

Air Flow: 5400 to 3600

Speed: 2

Mounting Type: Pedestal, Pedestal with Wheels & Wall

Color: Gray

Ship By: Free LTL Freight

