



**General Characteristics of Reversible Belt, Belt Drive Intake/Exhaust Fan**

The Triangle Reversible Belt is a belt drive Intake/Exhaust Fan. Used for industrial and commercial use. For indoor use. Perfect for use where both supply and exhaust are needed out of the same fan. Comes with a standard galvanized wall housing, welded construction and finished with a polyester powder-coat protection. Comes in 3 different sizes 30", 36" & 48". Designed with a standard reversible switch, bi-directional venturi, bi-directional airfoil blades and reversible totally enclosed motor. Includes pillow block bearings. Available in single or three-phase. Has a standard wall housing.

**Product Applications of Reversible Belt, Belt Drive Intake/Exhaust Fan**

For industrial and commercial use. Used where supply and exhaust are needed from the same fan. Used for indoor use.

**Warranty of Reversible Belt, Belt Drive Intake/Exhaust Fan**

Manufacturer's Warranty: 1 year.



**Specific Characteristics of Reversible Belt, Belt Drive Intake/Exhaust Fan**

Item #	Manufacturing #	Blade Dia. (In.)	CFM			Volts V	Amperes A	Phases Ph	HP	RPM	Weight and Dimensions with Packaging	
			0	0.125	0.25						Lbs.	L,W,H (In.)
<b>USRVE-001</b>	FHIR3015T-U-BD	30	8400	7200	5500	115/230	6.4/3.2	1	1	980	250	32,38,38
<b>USRVE-002</b>	FHIR3015T-X-BD	30	8400	7200	5500	230/460	6.4/3.2	3	1	980	250	32,38,38
<b>USRVE-003</b>	FHIR3017T-U-BD	30	10700	9800	8800	115/230	12.9/6.4	1	2	1250	255	32,38,38
<b>USRVE-004</b>	FHIR3017T-X-BD	30	10700	9800	8800	230/460	12.9/6.4	3	2	1250	255	32,38,38
<b>USRVE-005</b>	FHIR3615T-U-BD	36	11100	9800	8300	115/230	6.4/3.2	1	1	821	280	32,44,44
<b>USRVE-006</b>	FHIR3615T-X-BD	36	11100	9800	8300	230/460	6.4/3.2	3	1	821	280	32,44,44
<b>USRVE-007</b>	FHIR3617T-U-BD	36	14000	13200	11900	115/230	12.9/6.4	1	2	1035	285	32,44,44
<b>USRVE-008</b>	FHIR3617T-X-BD	36	14000	13200	11900	230/460	12.9/6.4	3	2	1035	285	32,44,44



**Reversible Belt  
 Belt Drive Intake/Exhaust Fan**  
 Data Sheet

<b>USRVE-009</b>	FHIR4815T-U-BD	48	19800	16300	8500	115/230	6.4/3.2	1	1	493	330	36,56,56
<b>USRVE-010</b>	FHIR4815T-X-BD	48	19800	16300	8500	230/230	6.4/3.2	3	1	493	330	36,56,56
<b>USRVE-011</b>	FHIR4817T-U-BD	48	24800	22100	18300	115/230	12.9/6.4	1	2	616	335	36,56,56
<b>USRVE-012</b>	FHIR4817T-X-BD	48	24800	22100	18300	230/460	12.9/6.4	3	2	616	335	36,56,56
<b>USRVE-013</b>	FHIR4818T-U-BD	48	28300	26100	23400	115/230	19.4/9.7	1	3	706	375	36,56,56
<b>USRVE-014</b>	FHIR4818T-X-BD	48	28300	26100	23400	115/230	19.4/9.7	3	3	706	375	36,56,56

**Specific Characteristics of Reversible Belt, Belt Drive Intake/Exhaust Fan**

Series	Length A	Width B	Height C
USRVE-001 to 004	30"	36 3/8"	36 3/8"
USRVE-005 to 008	30"	42 3/8"	42 3/8"
USRVE-009 to 014	34"	54 3/8"	54 3/8"

