

General Characteristics of Reversible Direct, Direct Drive Intake/Exhaust Fan

The Triangle Reversible Direct is a direct drive Intake/Exhaust Fan. Used for industrial and commercial use. For indoor use. Perfect for use where both supply and exhaust are needed out of the same fan. Comes with a standard galvanized wall housing, welded construction and finished with a polyester powder-coat protection. Comes in 3 different sizes 30", 36" & 48". Designed with a standard reversible switch, bi-directional venturi, bi-directional airfoil blades and reversible totally enclosed motor. Includes pillow block bearings. Available in single or three-phase. Has a standard wall housing.

Product Applications of Reversible Direct, Direct Drive Intake/Exhaust Fan

For industrial and commercial use. Used for indoor use.

Warranty of Reversible Direct Direct, Drive Intake/Exhaust Fan

Manufacturer's Warranty: 1 year.



Specific Characteristics of Reversible Direct, Direct Drive Intake/Exhaust Fan

Item #	Manufacturing #	Blade Dia. (In.)	CFM			Volts V	Amperes A	Phases Ph	HP	RPM	Weight and Dimensions with Packaging	
			0	0.125	0.25						Lbs.	L,W,H (In.)
			USRDD-001	FHIR3015T-U-DD	30						8700	8000
USRDD-002	FHIR3015T-X-DD	30	8700	8000	7000	230/460	6.4/3.2	3	1	1160	270	32,38,38
USRDD-003	FHIR3017T-U-DD	30	11500	10750	9500	115/230	12.9/6.4	1	2	1160	320	32,38,38
USRDD-004	FHIR3017T-X-DD	30	11500	10750	9500	230/460	12.9/6.4	3	2	1160	320	32,38,38
USRDD-005	FHIR3615T-U-DD	36	12500	11800	8400	115/230	6.4/3.2	1	1	860	315	32,44,44
USRDD-006	FHIR3615T-X-DD	36	12500	11800	8400	230/460	6.4/3.2	3	1	860	315	32,44,44
USRDD-007	FHIR3617T-U-DD	36	13500	12700	11800	115/230	12.9/6.4	1	2	1160	340	32,44,44
USRDD-008	FHIR3617T-X-DD	36	13500	12700	11800	230/460	12.9/6.4	3	2	1160	340	32,44,44
USRDD-009	FHIR4815T-U-DD	48	14900	12700	10600	115/230	6.4/3.2	1	1	860	365	36,56,56
USRDD-010	FHIR4815T-X-DD	48	14900	12700	10600	230/460	6.4/3.2	3	1	860	365	36,56,56
USRDD-011	FHIR4817T-U-DD	48	22200	20100	17900	115/230	12.9/6.4	1	2	860	390	36,56,56
USRDD-012	FHIR4817T-X-DD	48	22200	20100	17900	230/460	12.9/6.4	3	2	860	390	36,56,56



USRDD-013 FHIR4818T-X-DD 48 28100 26200 23900 230/460 9.7/4.8 3 3 860 405 36,56,56

Specific Characteristics of Reversible Direct, Direct Drive Intake/Exhaust Fan

Series	Length A	Width B	Height C
USRDD-001 to 004	30"	36 3/8"	36 3/8"
USRDD-005 to 008	30"	42 3/8"	42 3/8"
USRDD-009 to 013	34"	54 3/8"	54 3/8"

